

## CaviBlaster 1228-G

Gasoline Engine, 12 GPM & 2,800-PSI

### Specifications and Options

Our most popular commercial unit, is a compact and lightweight system with superior cleaning performance utilizing the Ultra-Cavitation technology

#### Accessories Included:

Feed Hose (15 feet) with electric suction pump, By-Pass Hose (15 feet), High Pressure Hose (50 feet), Zero-Thrust Balanced Gun, Battery Start

#### Optional Accessories:

Additional pressure hose available in 50 ft or 100 ft sections  
Max. Pressure hose length recommended up to 300 ft (100 meters) total



SKID Dimensions	
Length w/o Handle	35" / 89 cm
Length w/ Handle	45" / 114 cm
Width	26" / 66 cm
Height	29" / 74 cm
Weight	280 Lbs / 127 Kg

Pump System	
Pressure Pump	General TSF 2421 Plus
Pump Mat. / Type	Triplex Plunger - Brass
Flow Rate	12 GPM / 45 LPM
Pressure	2,800-PSI / 193 BAR
Hose Diam/Max Lgth	1/2" - 300 ft / 100 meters

Shipping Dimensions	
Pallet 48" x 40" x 40"	400 Lbs / 182 Kgs

Drive System	
Engine	Honda GX690 / iGX800
Engine Type	2-cylinder air-cooled
Intake System	Naturally aspirated
Combustion System	Electronic Fuel Injection
Power Output Max	28 HP / 21 kW
Power Output Cont.	24 HP / 18 kW
Clutch Type	Belt Drive
Starting System	Electric

Feed System	
Feed Pump	Johnson L2200
Pump Material	Thermoplastic, SS Shaft
Flow Rate @ Max Lift	29gpm/110L/m @ 3.3Lft/1m
Pump Power supply	12V @ 7.5Amp

Ideal For
Small to Mid size Boat Hulls
Piers, Pilings & Seawalls
Running Gear & Out drivers
Pools & Indoor Underwater Instalations



Tool Options
Zero-Thrust Balanced Gun
Double Un-Balanced Guns
Single CaviDome
ROV Lance

**\*PRICING AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE**

